

SECTION I- PRODUCT IDENTIFICATION

PRODUCT NAME: NU-GLAZE STAIN.
PRODUCT CODE: PPD 700, 701, 702, 703, 704, 705, 706, 707, 708
FACTORY CODE: 541-100, 541-207, 541-203
MANUFACTURER'S NAME: DOVER FINISHING PRODUCTS
3245 J B DESCHAMPS
LACHINE, QUEBEC
H8T 3E4

INFORMATION PHONE:
SIMDUT: **CLASS B-2** FLAMMABLE LIQUID WITH A FLASH POINT INFERIOR TO 37 C.
CLASS D-2b TOXIC SUBSTANCE HAVING VARIOUS EFFECTS.

DOT NAME: CLASS 3 FLAMMABLE LIQUID
SHIPPING NAME: PAINTS OR PAINTING RELATED MATERIALS UN1263 PGII
ISSUE DATE 2008-05-13

SECTION 1A- FIRST AID MEASURES

EYE CONTACT: Rinse eyes immediately with clear running water for at least 15 minutes, keeping eyelids open. Use cold water. If the victim is wearing contact lenses remove them, do not use eye drops, seek medical attention

SKIN CONTACT: After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the contaminated skin with running water and non-abrasif soap. Be particularly careful to clean folds, crevices, creases, and groin. cover the irritated skin with an emolient. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

HAZARDOUS SKIN CONTACT: No additional information

SLIGHT INHALATION: Allow the victim to rest in a well ventilated area, seek immediate medical attention.

HAZARDOUS INHALATION: Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth to mouth resuscitation. **WARNING** It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

SLIGHT INGESTION: DO NOT induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

HAZARDOUS INGESTION: No additional information.

SECTION II- HAZARDOUS INGREDIENTS

NAME	CAS#	%WEIGHT	TLV / PEL	LD50 / LC50
Calcium resinate	9007-13-0	5-15	not available	not available
Naphta	64742-88-7	60-100	not available	not available

SECTION III - PHYSICAL DATA

Physical state and appearance Liquid
pH (1% soln/water) Neutral
Odor threshold Not available
Volatility 87.2% (v/v) Weighted average 69.5% (w/w) Weighted average.

Melting sublimation	not available
Boiling condensation point	not available
Specific gravity.	0.872 (Water = 1)
Vapor density	not available
Vapor pressure	not available
Water/oil dist coeff.	Not available
Dispersion properties	Will not dispersed in hot or cold water.
Solubility	Insoluable in hot or cold water

=====

SECTION IV -FIRE AND EXPLOSION DATA

The product is	Flammable
Auto-ignition temperature	not available
Fire degradation products	not available
Flash points	The lowest known value is (CLOSED CUP) 40 deg C. (Naphta)
Flammable limits	not available
Fire extinguishing procedures	Explosive. Flammable liquid, insoluble in water. SMALL FIRES: Use Dry chemicals, CO2, Alcohol foam or water. LARGE FIRES: Use Alcohol foam, water spray or fog. Cool containers with water fog to avoid overpressure, auto-ignition or explosion. Do not fight fire evacuate the area.
Flammibility	Highly flammable in presence of open flames and sparks and in the presence of combustibles
Risk of explosion	Highly explosive in presence of open flames and sparks, of shocks.

=====

SECTION V - REACTIVITY DATA

STABILITY: The product is stable.

HAZARDOUS DECOMP. OR BYPRODUCTS: Not available

PRODUCTS OF DEGRADATION: Possible hazardous short term degradation products are not anticipated. However, long term degradation products may arise.

CORROSIVITY: No specific information about the corrosivity of the product is available.

REACTIVITY: Highly reactive with oxidizing agents, combustibles, metals.
Non-reactive with reducing agents, organic substances, acids, alkalis, moisture.

=====

SECTION VI - PREVENTIVE MEASURES

WASTE DISPOSAL: Waste material must be disposed of in accordance with Federal, Provincial, and Local enviromental control regulations. Empty containers should be recycled or disposed of through an approved waste management facility.

STORAGE: Do not store above 48 deg. C. Keep in a cool well-ventilated place. Highly toxic materials should be stored in a separate locked safety cabinet or room.

PRECAUTIONS: Keep locked up. Keep away form sources of ignition. Do not ingest. Do not breath fumes or vapor or spray. Take precautionary measures against electrostatic discharges. In case of insufficient ventilation , wear suitable respiratory equipement. If ingested, seek medical advice immidiately. Avoid contact with eyes and skin. Keep away from incompatibles such as oxidizing agents, reducing agents, organic materials, metals, acids, alkalis, moisture.

SPILLS OR LEAKS.
Small spill or leak. Absorb with an inert material and put the spilled material in an appropraite waste disposal container.
Large spill or leak. Provide maximum ventilation. Only personnel equipped with proper respiratory equipement should be permitted in the area. Remove all sourced of ignition. Stop leak if without risk.
Absorb with DRY earth, sand, or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or other confined areas. Call local authorities for assistance on disposal.

PROTECTIVE CLOTHING IN CASE OF SPILL: Splash goggles. Full suit. Vapor and dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficent, consult a specialist BEFORE handling this product.

SECTION VII - PROTECTIVE MEASURES

RESPIRATORY PROTECTION:

Overexposure to vapors may be prevented by ensuring ventilation controls, vapor exhaust or fresh air entry. If TLV of any component is exceeded, use an appropriate NIOSH / MSHA approved respirator. Follow respirator manufacturers directions for respirator use.

VENTILATION:

Provide sufficient mechanical and or local exhaust ventilation to keep the concentration of ingredients listed in section II below the lowest exposure limits.

PROTECTIVE GLOVES:

Use impermeable chemical handling gloves for skin protection.

EYE PROTECTION: Use Chemical safety glasses, goggles, faceshields for eye protection.

OTHER PROTECTIVE CLOTHING OR EQUIPEMENT:

Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of head caps whenever possible is strongly recommended. Clean or dicard contaminated cltohing and shoes.

WORK / HYGIENIC PRACTICES

Eye washes and safety showers in the workplace are recommended.

=====

SECTION VIII - DISCLAIMER

The information and recommendations contained herein are believed to be accurate at the time of the preparation or obtained from sources believed to be generally reliable. DOVER FINISHING PRODUCTS will not be held liable for claims relating to any party's use of, or reliance on information contained herein, regardless of whether it is claimed the information is inaccurate.