



SECTION I- PRODUCT IDENTIFICATION

PRODUCT NAME: LAC-FRENCH 77700X
PRODUCT CODE: PPD 807
FACTORY CODE: T10-188
MANUFACTURER'S NAME: DOVER FINISHING PRODUCTS
3245 J B DESCHAMPS
LACHINE, QUEBEC
H8T 3E4

INFORMATION PHONE: (514) 420-6030
SIMDUT: **CLASS B-2** FLAMMABLE LIQUID WITH A FLASH POINT INFERIOR TO 37C.
HAZARDOUS **CLASS D-1A** VERY TOXIC SUBSTANCE HAVING IMMEDIATE EFFECTS.
CLASS D-2A, D-2B TOXIC SUBSTANCE HAVING VARIOUS EFFECTS.

DOT NAME: CLASS 3 FLAMMABLE LIQUID
SHIPPING NAME: PAINTS OR PAINTING RELATED MATERIALS UN1263 PGII
DATE REVISED: 2009-10-26

SECTION 1A- FIRST AID MEASURES

EYE CONTACT: Rinse eyes immediately with clear running water for at least 15 minutes, keeping eyelids open. Use cold water. If the victim is wearing contact lenses remove them, do not use eye drops, seek medical attention
SKIN CONTACT: After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases, and groin. cover the irritated skin with an emollient. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.
HAZARDOUS SKIN CONTACT: No additional information
SLIGHT INHALATION: Allow the victim to rest in a well ventilated area, seek immediate medical attention.
HAZARDOUS INHALATION: Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth to mouth resuscitation. **WARNING** It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.
SLIGHT INGESTION: DO NOT induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
HAZARDOUS INGESTION: No additional information.

SECTION II- HAZARDOUS INGREDIENTS

NAME	CAS#	%WEIGHT	TLV / PEL	LD50 / LC50
ACETONE	67-64-1	30-60	TWA:750 STEL 1000 TWA: 1780 STEL 2380 MG/M3 FROM ACGIH	ORAL (LD50) ACUTE 3000 MG/KG (MOUSE). DERMAL (LD50) ACUTE 20000 MG/KG (RABBIT). VAPOR (LC50) 29853 PPM 4HRS (RAT)
ETHANOL	64-17-5	30-60	TWA: 1000 PPM FROM ACGIH (TLV)	ORAL(LD50) ACUTE 8000 MG/KG (RAT). VAPOR (LC50) ACUTE 8000 PPM 4HRS (RAT)
METHANOL	67-56-1	5-15	TWA:200 PPM	ORAL(LD50) ACUTE 6200



TWA:1262 MG/M3
FROM ACGIH

MG/KG (RAT) DERMAL (LD50)
ACUTE 15800 MG/KG (RABBIT)
VAPOR (LC50) ACUTE 64000
PPM 4 HRS. (RAT)

SECTION III - PHYSICAL DATA

Physical state and appearance	Liquid
pH (1% soln/water)	Neutral
Odor threshold	Highest known value is 2 ppm (Acetone)
Volatility	81% (P/P)
Melting sublimation	may start to solidify at -95.35 deg C (Acetone)
Boiling condensation point	Lowest known value is 56.2 deg C (Acetone)
Specific gravity.	0.86 (Water = 1)
Vapor density	Highest known value is 2 (air = 1) (acetone)
Vapor pressure	Highest known value is 186.2 mm of Hg (@ 20 deg C) (acetone)
Water/oil dist coeff.	Not available
Dispersion properties	Will not disperse in methanol
Solubility	Easily soluble in hot, or cold water, methanol, diethyl ether. Partially soluble in n-octanol.

SECTION IV -FIRE AND EXPLOSION DATA

The product is	Flammable
Auto-ignition temperature	Lowest known value is 422 deg C (Ethanol)
Fire degradation products	These products are known Carbon Oxides (CO, CO2)
Flash points	The lowest known value is (CLOSED CUP) -18 deg C. (acetone)
Flammable limits	greatest known range is LOWER 6% UPPER 36.5% (methanol)
Fire extinguishing procedures	Flammable liquid, Explosive. Soluble in water SMALL FIRES: Use Dry chemicals, CO2, Alcohol foam or water. LARGE FIRES: Use Alcohol foam, water spray or fog. Cool containers with water fog to avoid overpressure, auto-ignition or explosion. Do not fight fire evacuate the area.
Flammability	Highly flammable in presence of open flames and sparks and in the presence of combustibles
Risk of explosion	Highly explosive in presence of open flames and sparks, of shocks.

SECTION V - REACTIVITY DATA

STABILITY: The product is stable
HAZARDOUS DECOMP. OR BYPRODUCTS: Not available
PRODUCTS OF DEGRADATION: Possible hazardous short term degradation products are not anticipated. However, long term degradation products may arise.
CORROSIVITY: No considered corrosive for glass.
REACTIVITY: Slightly reactive with acids, alkalis, and moisture. Highly reactive with reducing agents.

SECTION VI - PREVENTIVE MEASURES

WASTE DISPOSAL: Waste material must be disposed of in accordance with Federal, Provincial, and Local environmental control regulations. Empty containers should be recycled or disposed of through an approved waste management facility.
STORAGE: Do not store above 48 deg. C. Keep in a cool well-ventilated place. Highly toxic materials should be stored in a separate locked safety cabinet or room.
PRECAUTIONS: Keep locked up. Keep away from sources of ignition. Do not ingest. Do not breath fumes or vapor or spray. Take precautionary measures against electrostatic discharges. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately. Avoid



contact with eyes and skin. Keep away from incompatibles such as oxidizing agents, reducing agents, organic materials, metals, acids, alkalis, moisture.

SPILLS OR LEAKS.

Small spill or leak. Absorb with an inert material and put the spilled material in an appropriate waste disposal container.

Large spill or leak. Provide maximum ventilation. Only personnel equipped with proper respiratory equipment should be permitted in the area. Remove all sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand, or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or other confined areas. Call local authorities for assistance on disposal.

PROTECTIVE CLOTHING IN CASE OF SPILL: Splash goggles. Full suit. Vapor and dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient, consult a specialist BEFORE handling this product.

=====
SECTION VII - PROTECTIVE MEASURES

RESPIRATORY PROTECTION:

Overexposure to vapors may be prevented by ensuring ventilation controls, vapor exhaust or fresh air entry. If TLV of any component is exceeded, use an appropriate NIOSH / MSHA approved respirator. Follow respirator manufacturer's directions for respirator use.

VENTILATION:

Provide sufficient mechanical and or local exhaust ventilation to keep the concentration of ingredients listed in section II below the lowest exposure limits.

PROTECTIVE GLOVES:

Use impermeable chemical handling gloves for skin protection.

EYE PROTECTION: Use Chemical safety glasses, goggles, faceshields for eye protection.

OTHER PROTECTIVE CLOTHING OR EQUIPEMENT:

Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of head caps whenever possible is strongly recommended. Clean or discards contaminated clothing and shoes.

WORK / HYGIENIC PRACTICES

Eye washes and safety showers in the workplace are recommended.

=====
SECTION VIII - DISCLAIMER

The information and recommendations contained herein are believed to be accurate at the time of the preparation or obtained from sources believed to be generally reliable. DOVER FINISHING PRODUCTS will not be held liable for claims relating to any party's use of, or reliance on information contained herein, regardless of whether it is claimed the information is inaccurate.