

Material Safety Data Sheet

Identity

Quick Cure Wood Epoxy

Section I - Chemical Product and Company Identification

<i>Manufacturer's Name</i> Dover Finishing Products	<i>Date Revised</i> 2015-05-15
<i>Address</i> 16789-A Hymus Kirkland, Quebec, H9H 3L4	<i>Telephone Number for information</i> 514-420-6030

Section II - Hazardous Ingredients/Identity Information

<i>Chemical Name</i>	<i>CAS #</i>	<i>Weight % (less than)</i>
Glycidyl ethers of bisphenol A resins	25068-38-6	10-30%
Tri(dimethylaminomethyl) phenol	90-72-2	1-5%

TLV (Threshold limit value) - Short Term: 500-1000 PPM, Long Term: 250-400 PPM

Section III - Physical/Chemical Characteristics

<i>Boiling Point</i> N/A		<i>Specific Gravity (H2O)</i> .95
<i>Vapor Pressure (mm Hg)</i> N/A	N/A	<i>Melting Point</i>
<i>Vapor Density</i> N/A		<i>Evaporation Rate (Butyl Acetate = 1)</i> N/A
<i>Solubility in water</i> Insoluble		<i>VOC's (Volatile Organic Compounds) by weight</i> < 1%
<i>Appearance and odor</i> Beige/White Putty		<i>VHAP (Volatile Hazardous Air Pollutants) by weight</i> None

Section IV - Fire and Explosion Hazard Data

<i>Flash Range</i> N/A	<i>Flammable Limits</i>	<i>LEL</i> 1.1%	<i>UEL</i> 7%
<i>Extinguishing Media</i> Carbon Dioxide, Foam, Dry Chemical			
<i>Special Fire Fighting Procedures</i> Firefighters should wear self-contained breathing gear and protective clothing.			
<i>Unusual Fire & Explosion Hazards</i> N/A			

Section V - Reactivity Data

<i>Stability</i>	<i>Unstable</i>		<i>Conditions to avoid</i>
	<i>Stable</i>	X	None
<i>Incompatibility (Materials to avoid)</i> N/A			
<i>Hazardous Decomposition or byproducts</i> Carbon monoxide, aldehydes, acids, oxides of sulfur or nitrogen			
<i>Hazardous M</i> <i>Polymerization</i>	<i>ay occur</i>		<i>Conditions to avoid</i>
	<i>Will not occur</i>	X	

Quick Cure Wood Epoxy

Section VI - Health Hazard Data

<i>Lethal Dose information (mg/kg)</i>	<i>Oral</i>	<i>Skin</i>	<i>Inhale</i>		
Glycidyl ethers of bisphenol A resins	RAT - 11400.00	20.00	N/est		
Tri (dimethylaminomethyl) phenol	RABBIT - 1635.00	8.00	0.50		
<i>Permissible exposure limit</i>	<i>ACGIH TLV-C</i>	<i>ACGIH STEL</i>	<i>OSHA STEL</i>	<i>OSHA PEL</i>	
Glycidyl ethers of bisphenol A resins	N/est	N/est	N/est	N/est	
Tri (dimethylaminomethyl) phenol	N/est	N/est	N/est	N/est	

Effects of Overexposure

Ingestion: Irritation of intestinal tract
 Inhalation: None
 Skin and Eyes: Possible irritant and sensitizer
Emergency First Aid Procedures
 INGESTION: Seek medical advice
 INHALATION: Remove to fresh air.
 SKIN: Wash with water and wash with soap.
 EYES: Flush with plenty of water, contact a physician.

Section VII - Precautions for Safe Handling and Use

Steps to be taken if Material is released or Spilled
 N/A

Waste Disposal Methods

Landfill or incinerate in accordance with EPA and local regulations.

Precautions to be taken in Handling and Storing

Store in a cool, dry place. Keep container closed when not in use. Keep well ventilated. Keep away from children.

Section VIII - Personal Protection

Respiratory Protection (specify type)

None required unless sanding or abrading

<i>Ventilation Local</i>	<i>Exhaust</i>	<i>Special</i>
<i>M</i>	Local exhaust recommended.	
	<i>mechanical (general)</i>	<i>Other</i>

Protective Gloves Eye

Resistant plastic or rubber.

Protection
 Safety glasses

Other Protective Clothing or Equipment

N/A.

Work/Hygiene Practice

Wash hands with soap and water before eating or smoking

Section IX - Regulatory Information

VHAP's Information

HAP's Compliant